



SPECIFICATIONS

MATTRESS TYPE: CONSTRUCTION
MATTRESS DIMENSIONS: 8' X 20' X 12"
MATTRESS WEIGHT: AIR 13,200 POUNDS
CONCRETE DENSITY: 145 LBS. PER CU. FT., 4,000 PSI
160 ELEMENTS: 5/8" ULTRA VIOLET STABILIZED COPOLYMER
EXTRUDED FIBER ROPE, MINIMUM TENSILE STRENGTH 9,500 POUNDS

805 Dunn Street
 Houma, LA 70360
 Ph. 985-868-0001
 Fax 985-851-0108
 Email: submar@submar.com
 Website: www.submar.com



SUBMAR
STANDARD 8.00'x20.00'
MAT DETAIL

12" CONCRETE MATTRESS

COPYRIGHT © SUBMAR, INC. 2010 ALL RIGHTS RESERVED.

THESE CONCEPTUAL DRAWINGS ARE PREPARED BY SUBMAR
 FOR ESTIMATING PURPOSES ONLY AND ARE NOT CONSTRUCTION DRAWINGS.
 THESE CONFIDENTIAL DRAWINGS MAY NOT BE COPIED UNLESS APPROVED BY SUBMAR, INC.

DATE: 01/03/13	CHECKED BY: DWD	DRAWN BY: KPF	SCALE: N.T.S.	CONTACT:	PHONE: #:
-------------------	--------------------	------------------	------------------	----------	-----------