



### SPECIFICATIONS

**MATTRESS TYPE:** CONSTRUCTION  
**MATTRESS DIMENSIONS:** 8' X 20' X 9"  
**MATTRESS WEIGHT:** AIR 10,500 POUNDS  
**MATTRESS WEIGHT SUBMERGED:** 6,000 POUNDS (APPROX.)  
**CONCRETE DENSITY:** 145 LBS. PER CU. FT., 4,000 PSI  
**160 ELEMENTS:** 5/8" ULTRA VIOLET STABILIZED COPOLYMER  
**EXTRUDED FIBER ROPE,** MINIMUM TENSILE STRENGTH 9,500 POUNDS

805 Dunn Street  
 Houma, LA 70360  
 Ph. 985-868-0001  
 Fax 985-851-0108  
 Email: [submar@submar.com](mailto:submar@submar.com)  
 Website: [www.submar.com](http://www.submar.com)



**SUBMAR**  
**STANDARD 8.00'x20.00'**  
**MAT DETAIL**

**9" CONCRETE MATTRESS**

THESE CONCEPTUAL DRAWINGS ARE PREPARED BY SUBMAR

FOR ESTIMATING PURPOSES ONLY AND ARE NOT CONSTRUCTION DRAWINGS.

THESE CONFIDENTIAL DRAWINGS MAY NOT BE COPIED UNLESS APPROVED BY SUBMAR, INC.

COPYRIGHT © SUBMAR, INC. 2013 ALL RIGHTS RESERVED.

DATE: 01/03/13

CHECKED BY: DWD

DRAWN BY: KPF

SCALE: N.T.S.

CONTACT:

PHONE: #: